



Product data sheet. Synthetic Air.

Linde HiQ® specialty gases portfolio

Specifications

Component	Chemical formula	Unit	HiQ synthetic air 4.0	HiQ synthetic air 5.0	HiQ synthetic air 5.5
Air	$N_2 + O_2$	%	$\geq 99,99$	$\geq 99,999$	$\geq 99,9995$
Water	H_2O	ppm	≤ 5	≤ 5	≤ 2
Total hydrocarbons	C_nH_m	ppm		≤ 1	$\leq 0,1$
Carbon monoxide	CO	ppm			≤ 1
Carbon dioxide	CO_2	ppm			≤ 1


Material no.

Cylinder size	HiQ synthetic air 4.0	HiQ synthetic air 5.0	HiQ synthetic air 5.5
10 litres	—	116794	116797
20 litres	116792	116795	116798
50 litres	116793	116796	116799
50 litres with batch certificate	—	—	118186
12x50 litres (bundle)	—	118181	—

Features

Valve outlet: DIN 477 No. 13

Cylinder colour: Light Green/Silver grey



Characteristics

Compressed gas

Filling pressure: 200 bar

Safety

For all safety related topics including handling, transport and recommended use please see Safety Data Sheets.

Sweden: www.linde-gas.se/sakerhetsdatablad

Norway: www.linde-gas.no/sikkerhetsdatablader

Finland: www.linde-gas.fi/turvallisuusohjeet

Denmark: www.linde-gas.dk/sikkerhedsdatablade

Iceland: www.linde-gas.is/oryggisleidbeiningar

Latvia: www.linde-gas.lv/drosibas_datu_lapas

Lithuania: www.linde-gas.lt/saugos_duomenu_lapai

Estonia: www.linde-gas.ee/ohutuskaardid

Safety Data Sheets are available through your local Linde homepage in both local language and English.



Linde Northern Europe, www.linde-gas.com

® HiQ is a registered trademarks of Linde plc or its affiliates.